


Instrument Data Sheet

General	1	Product	Vertical Belt Alignment Control – Cast Aluminum
	2	Model Number	VA
	3	Manufacturer	Conveyor Components Company
	4		
Environment	5	Operating Temperature	-10 to 82 °C [14 to 179 °F]
	6	Chassis Material	Cast Aluminum 319
	7	Microswitch Enclosure Material	Powder coated aluminum
	8	Microswitch Enclosure Rating	NEMA Type 3, 4, 4X, 6P, 13 (Marked on microswitch housing)
	9	Mounting	Six holes at $\varnothing^{13/32}$ [10 mm]; mounted through chute wall
	10		
Electrical	11	Switch Type	Sequential double break (different activating position for each pole)
	12	Contact Type	Dry contact
	13	Contact Rating	Max 600 VAC: 360 VA 250 VDC: 0.15A ind, 0.4A res 125 VDC: 0.25A ind, 0.8A res 24 VDC: 10A
	14	Electrical Action	Non-latching
	15	Electrical Connection	One $\frac{3}{4}$ " NPT internal thread
	16	Indicating Lamp	None
	17		
	18		
Actuator	20	Type	Belt alignment control for vertical belts
	21	Mechanism	$\varnothing 2.5$ " [64 mm] Roller on spring-return lever
	22	Inactivated State	Field-adjustable roller pitch: 25° to 90° from vertical
	23	Pole 1 Activation State	15° from resting position
	24	Pole 2 Activation State	25° from resting position
	25	Action	Non-latching
	26		
	27		
	28		
Options	30	Finish	Uncoated (standard) or epoxy coating (Option E)
	31		
	32		
	33		
	34		
	35		
Certifications	36		
	37	UL Certification File	Microswitch: E37138
	38		
Manufacturer	39		
	40		Conveyor Components Company Division of Material Control, Inc 130 Seltzer Road, PO Box 167 Croswell, MI 48422 USA (810) 679-4211 info@conveyorcomponents.com www.conveyorcomponents.com
Notes: 1. Typically used in pairs to provide proper protection.			