


Instrument Data Sheet

General	1	Product	Vinyl Coated Pull Cord Cable
	2	Model Number	RS-26
	3	Manufacturer	Conveyor Components Company
	4		
Specifications	5	Cable Material	Galvanized steel aircraft cable
	6	Coating Material	Nylon
	7	Coating Color	Orange
	8	Cable size	3/32" [2.4 mm]
	9	Strands	7x7
	10	Outside Diameter	3/16" [4.8 mm]
	11	Breaking Strength	920 lb [417 kg]
	12		
	13		
	14		
	15		
	16		
	17		
	18		
	19		
	20		
	21		
	22		
	23		
	24		
Options	25	Coating Color	Orange (standard)
	26		Red (option R)
	27		
	28		
	29		
Accessories	30	Support Eyebolt	1/2" x 6" Plated, with (2) hex nuts and (1) lock washer (RS-27)
	31		Threadless (no hardware required): 5/16" x 9" Plated (RS-23)
	32	End fitting	Cable clamp (RS-28)
	33		
	34		
	35		
	36		
	37		
	38		
	39		
Manufacturer	40		Conveyor Components Company Division of Material Control, Inc. 130 Seltzer Road, PO Box 167 Croswell, MI 48422 USA (810) 679-4211 info@conveyorcomponents.com www.conveyorcomponents.com
Notes: 1. Cable must be supported with eyebolts. Maximum spacing: 10' [3 m]. 2. Maximum of 100' [30.5 m] of cable may be attached to each side of the unit; 200' [61 m] total.			